

208~230 Compact 8-Way Cassette


Model:GMV-ND18T/E-T(U)



Specifications	Unit	Parameter
Model	—	GMV-ND18T/E-T(U)
Performance		
Rated Cooling Capacity	kBtu/h	18
Rated Heating Capacity	kBtu/h	20
Sound Pressure Level	dB(A)	39/41/43
Electrical Data		
Power Supply	Voltage,Phase, Hertz	208/230,1,60
Maximum Overcurrent Protection (MOP)	A	15
Minimum Circuit Amps (MCA)	A	0.8
Fan		
Type x Quantity	—	Centrifugal×1
Air Flow Volume	CFM	330/385/430
Fan Motor Running Current	A	0.6
Fan Motor Power Output	W	63
Refrigerant Piping		
Connection Pipe	Gas(mm/inch)	φ15.9/φ5/8
	Liquid(mm/inch)	φ9.52/φ3/8
Connection method	—	Flare Connection
Refrigerant	—	R410A
Dimension/Weight		
Dimensions (H×W×D)	mm/inch	265×570×570 (10-7/16×22-7/16×22-7/16)
Net Weight	kg/lbs	17.5/38.6
Other		
Safety Certification	—	ETL

Job Name:		Date:	
System Reference No.:			
Engineer Signature:			

Outline and Physical Dimensions of GMV-ND18T/E-T(U).



model	H
GMV-ND18T/E-T(U)	280 (11-1/32)

Unit:mm(in.)

